


FACTORS AFFECTING THE EFFICIENCY OF KRYPTON HALL THRUSTERS

RICHARD R. HOFER, PETER Y. PETERSON

QSS GROUP, INC., CLEVELAND, OH

DAVID T. JACOBSON, DAVID M. MANZELLA

NASA GLENN RESEARCH CENTER, CLEVELAND, OH



46TH MEETING OF THE APS DIVISION OF PLASMA PHYSICS, SAVANNAH, GA, NOV. 15-19, 2004

GLENN RESEARCH CENTER AT LEWIS FIELD




PAYLOAD ADVANTAGE – MARS

- NUCLEAR ELECTRIC PROPULSION DELIVERS GREATER PAYLOADS THAN CHEMICAL PROPULSION AT THE EXPENSE OF TRIP TIME.
- SPECIFIC IMPULSE OF 4000 s BALANCES TRIP TIME WITH DELIVERED PAYLOAD.
 - TYPICAL SPECIFIC IMPULSE FOR ION THRUSTERS
 - MORE THAN TWICE THE TYPICAL SPECIFIC IMPULSE OF XENON HALL THRUSTERS
- COMPARED TO ION THRUSTERS, HALL THRUSTERS OFFER BENEFITS IN TERMS OF VOLUME, MASS, AND COST

THE QUESTION:
HOW CAN HALL THRUSTERS
ACHIEVE HIGH-SPECIFIC IMPULSE
AND LONG LIFETIME?

ONE (POSSIBLE) ANSWER:
KRYPTON HALL THRUSTER



KRYPTON VS. XENON

	XENON	KRYPTON	RELATIVE TO XENON...
MOLECULAR WEIGHT (G/MOL)	131.3	83.8	$\uparrow I_{sp}$, $\downarrow T$, \uparrow LIFETIME (@ CONSTANT VOLTAGE AND DENSITY)
1 ST IONIZATION POTENTIAL (EV)	12.1	14.0	\downarrow MASS UTILIZATION EFFICIENCY, \downarrow MULTIPLY-CHARGED IONS (\uparrow LIFETIME)
COST (\$/L)	\$4.50	\$0.38	\downarrow QUALIFICATION & ON-ORBIT COSTS \uparrow AVAILABILITY, \downarrow PRICE VOLATILITY
DENSITY (@ 190 BAR, 340 K, KG/M ³)	1.66	0.67	\uparrow STORAGE TANK MASS/VOLUME


IN GENERAL,

$XE \rightarrow \text{HIGH-}\eta, \text{HIGH-}T$

$KR \rightarrow \text{HIGH-}I_{sp}, \text{LONG LIFE}$

THE KRYPTON EFFICIENCY CHALLENGE

EFFICIENT KRYPTON OPERATION REQUIRES INCREASING THE **PROPELLANT UTILIZATION**, WHICH IS AFFECTED BY SEVERAL DESIGN VARIABLES.




THE CHALLENGE IS TO ACHIEVE HIGH-PROPELLANT UTILIZATION WITHOUT SACRIFICING THERMAL MARGIN, STABILITY, AND LIFETIME.

NASA's HALL THRUSTERS

GRC-DEVELOPED HALL THRUSTERS HAVE DEMONSTRATED EFFICIENT
OPERATION OVER A WIDE RANGE OF CONDITIONS


POWER: 1-100 kW
THRUST: 0.1-3 N
 I_{sp} : 1000-5000 s
EFFICIENCY: 40-70%
PROPELLANT: Xe, Kr




PERFORMANCE – XENON VS. KRYPTON

- AT CONSTANT CURRENT DENSITY, EFFICIENCY INCREASES WITH THRUSTER SIZE (POWER)
- COMPARED TO XENON, KRYPTON EFFICIENCY IS TYPICALLY 5-15% LESS
- BOTH TRENDS ARE PRIMARILY DUE TO DIFFERENCES IN THE **MASS UTILIZATION**

XENON



KRYPTON



46TH MEETING OF THE APS DIVISION OF PLASMA PHYSICS, SAVANNAH, GA, NOV. 15-19, 2004

GLENN RESEARCH CENTER AT LEWIS FIELD



HALL THRUSTER EFFICIENCY

BY ACCOUNTING FOR THE EFFECTS OF A MULTIPLY-CHARGED, PARTIALLY-IONIZED PLASMA, HALL THRUSTER EFFICIENCY CAN BE EXPRESSED AS A FUNCTION OF THE CHARGE-, VOLTAGE-, CURRENT-, AND MASS-UTILIZATION EFFICIENCIES.

ANODE EFFICIENCY

$$\eta_a = \frac{T^2}{2\dot{m}_a P_d} = \eta_q \eta_v \eta_b \eta_m$$

CHARGE UTILIZATION EFFICIENCY

$$\eta_q = \frac{\left(\sum \Omega_i / \sqrt{Z_i} \right)^2}{\sum \Omega_i / Z_i}$$

VOLTAGE UTILIZATION EFFICIENCY

$$\eta_v = \frac{V_a}{V_d} = 1 - \frac{V_l}{V_d}$$

CURRENT UTILIZATION EFFICIENCY

$$\eta_b = \frac{I_b}{I_d}$$

MASS UTILIZATION EFFICIENCY

$$\eta_m = \frac{\dot{m}_b}{\dot{m}_a}$$

HALL THRUSTER EFFICIENCY (2)



ELECTRON CURRENT AND UTILIZATION EFFICIENCIES CAN BE COMPUTED IF THE FOLLOWING QUANTITIES ARE KNOWN:

- ✓ ANODE EFFICIENCY – MEASURED WITH THRUST STAND
- ✓ LOSS VOLTAGE – MEASURED WITH RPA
- ✓ ION SPECIES FRACTIONS – MEASURED WITH EXB PROBE



$$\eta_a = \underbrace{\left(1 - \frac{V_l}{V_d}\right)}_{\eta_v} \underbrace{\left(1 - \frac{I_e}{I_d}\right)^2 \left(\sum \frac{\Omega_i}{\sqrt{Z_i}}\right)^2}_{\eta_b \eta_m \eta_q} \frac{m_{xe} I_d}{\dot{m}_a e}$$

XENON

- CHARGE UTILIZATION = 98-99%
- MASS UTILIZATION = 86-90%
- VOLTAGE UTILIZATION = 89-97%
- CURRENT UTILIZATION = 77-81%



PLASMA DIAGNOSTICS IN VACUUM FACILITY 12



46TH MEETING OF THE APS DIVISION OF PLASMA PHYSICS, SAVANNAH, GA, NOV. 15-19, 2004
GLENN RESEARCH CENTER AT LEWIS FIELD



NASA-173Mv2 OPERATING CONDITIONS

- NASA-173Mv2 HALL THRUSTER

- MAGNETIC CIRCUIT OPTIMIZED FOR HIGH-ISP
- DESIGNED FOR XENON

- XENON CONDITIONS

- 800 V, 9.84 A
- 10 MG/S ANODE, 1 MG/S CATHODE
- THRUST 324 mN
- ANODE ISP 3310 s (TOTAL ISP = 3000 s)
- ANODE EFFICIENCY 66.7% (TOTAL EFFICIENCY = 59.6%)

- KRYPTON CONDITIONS

- 800 V, 8.27 A
- 6.4 MG/S ANODE, 0.64 MG/S CATHODE
- THRUST 215 mN
- ANODE ISP 3410 s (TOTAL ISP = 3100 s)
- ANODE EFFICIENCY 54.7% (TOTAL EFFICIENCY = 48.8%)




CONSTANT
NEUTRAL
DENSITY

NASA-173Mv2 – XENON VS. KRYPTON

$V_D = 800\text{ V}$	XENON	KRYPTON
LOSS VOLTAGE (V)	25	64
SPECIES FRACTIONS (%)	88, 11, 1	96.1, 3.4, 0.5
DIVERGENCE ANGLE (DEGREES)	61°	67°
BREATHING-MODE FREQUENCY (kHz)	25	31
OSCILLATION MAGNITUDE (% OF I_D)	15	14
ELECTRON CURRENT (A)	2.09	2.04

NASA-173Mv2 – XENON VS. KRYPTON EFFICIENCIES



$V_D = 800 \text{ V}$

10.5% DECREASE
IN MASS
UTILIZATION

46TH MEETING OF THE APS DIVISION OF PLASMA PHYSICS, SAVANNAH, GA, NOV. 15-19, 2004

GLENN RESEARCH CENTER AT LEWIS FIELD



CONCLUSIONS

- THE KRYPTON-FUELED HALL THRUSTER OFFERS THE POSSIBILITY OF HIGH-SPECIFIC IMPULSE AND LONG LIFETIME
- NASA'S SERIES OF HALL THRUSTERS HAVE DEMONSTRATED KRYPTON EFFICIENCIES ONLY 5-15% LESS THAN XENON
 - LARGER THRUSTERS HAVE SMALLER DIFFERENCES IN EFFICIENCY
- PLASMA MEASUREMENTS HAVE DEMONSTRATED THAT EFFICIENCY IS REDUCED DUE TO A DECREASE IN MASS UTILIZATION
- CURRENT EFFORTS ARE CONSIDERING THE IMPLICATIONS OF THESE RESULTS, AND HOW DESIGN CHANGES CAN BE MADE TO INCREASE THE EFFICIENCY OF KRYPTON HALL THRUSTERS

